

■ EK 120/42-L

Battery powered crimping tool 10 - 400 mm²

- C-head with 42 mm opening width
- For interchangeable dies, series 13, wide crimping
- Wide crimps mean 60% less crimps
- Easy handling by optimized position of centre of gravity
- Intelligent Pressing System "IPS"
- Automatic retraction stop (ARS)

Part No.	Crimping force	Crimping range mm ²	Stroke	Crimping cycle	Weight
EK12042L	120 kN	10 - 400	42 mm	approx. 8 s	6.8 kg

Please ask for dies series 13.

Scope of supply	Part No.
Battery 18 V / 3.0 Ah Li-Ion	RAL2
Charger for 18V Li-Ion Batteries	LGL1
Plastic case	KK120L

13
Klauke

400 mm²



Accessories:	Part No.
Mains adapter 18 V, 230 V mains operated	NG2230
USB-Adapter	PGA1
Digital meter for force and pressure measurement	TC1S
Measuring adapter series 13	MA120
Force sensor 130 kN	TF130L

■ ESG 55-L

Battery powered cutting tool 55 mm Ø

- Cuts armoured copper and aluminium cables and Al/St cables (ACSR)
- High performance, 18 V/3.0 Ah Li-Ion battery
- Closed cutting head with bolt interlock, rotates, flip top style
- Analysis of data via optical interface and USB adapter
- Manual retraction stop (MRS)

Part No.	Cutting force	Cutting range	Cutting cycle	Weight
ESG55L	120 kN	55 mm Ø	depending on cable type	1.7 kg

Scope of supply	Part No.
Battery 18 V / 3.0 Ah Li-Ion	RAL2
Quick charger for 18 V Li-Ion batteries	LGL1
Plastic case	KK120L

Cu/Al
Al/St

55 mm Ø



Accessories:	Part No.
Outer, stationary blade	ESG55EF
Inner, moving blade	ESG55ES
Mains adapter 18 V, 230 V mains operated	NG2230
USB-Adapter	PGA1

■ ESG 105-L

Battery powered cutting tool 105 mm Ø

- Cuts armoured copper and aluminium cables
- Large cutting range
- Closed cutting head with bolt interlock, rotates, flip top style
- Powerful motor for fast pressing cycles and efficient work
- Manual retraction stop (MRS)

Part No.	Cutting force	Cutting range	Cutting cycle	Weight
ESG105L	74 kN	105 mm Ø	depending on cable	4.2 kg

Scope of supply	Part No.
Battery 18 V / 3.0 Ah Li-Ion	RAL2
Quick charger for 18 V Li-Ion batteries	LGL1
Plastic case	MK105L

Cu/Al

105 mm Ø



Accessories:	Part No.
Outer, stationary blade	ESG105EF
Inner, moving blade	ESG105ES
Mains adapter 18 V, 230 V mains operated	NG2230
USB-Adapter	PGA1